



FASTENERS • ABRASIVES • TOOLS • SAFETY
YOUR INDUSTRIAL PARTNER

Trade and Distibutors welcome



086 100 FATS - 012 541 3336

info@fastenersdirect.co.za

www.fatsonline.co.za

201 Fairwood road

Rosslyn, Pretoria

2016
SEPTEMBER

INTRODUCING

SCHULZ COMPRESSORS

Bravo-CSL20BR-200



Air Displacement: 566 l/min
Max Pressure: 12 bar
No of Stages: 2
No of pistons: 2- L
Control: On-Off
Power: 5hp, 3.7kw
Poles: 2
Tank Volume: 200
Net Weight: 129.5 Kg
Gross Weight: 177 Kg
Width X Height X Length:
500 x 1020 x 1305 mm

R19999⁰⁰

PraticAir-CSL15-130



Air Displacement: 425 l/min
Max Pressure: 8.6 bar
No of Stages: 1
No of pistons: 2
Control: On-Off
Power: 3hp, 2.2kw
Poles: 2
Tank Volume: 130
Net Weight: 78 Kg
Gross Weight: 92 Kg
Width X Height X Length:
440 x 855 x 860 mm

R11999⁰⁰

Bravo-CSL30BR-250



Air Displacement: 850 l/min
Max Pressure: 12 bar
No of Stages: 2
No of pistons: 2- L
Control: On-Off
Power: 7.5hp, 5.5kw
Poles: 2
Tank Volume: 261
Net Weight: 192.5 Kg
Gross Weight: 263 Kg
Width X Height X Length:
630 x 1160 x 1580 mm

R28999⁰⁰

SRP-4015-Lean Reserv



Air Displacement: 1444 l/min
Max Pressure: 7.5 bar
Discharge Connection: 1"
Power: 15hp
Noise: 70
Width X Height X Length:
841 x 935 x 700 mm

R79999⁰⁰

LIMITED STOCK

Bravo-CSL40BR-250



Air Displacement: 1133 l/min
Max Pressure: 12 bar
No of Stages: 2
No of pistons: 2- L
Control: On-Off / Load -Unload
Power: 10hp, 7.5kw
Poles: 2
Tank Volume: 261
Net Weight: 235 Kg
Gross Weight: 305 Kg
Width X Height X Length:
630 x 1160 x 1570 mm

R32999⁰⁰

SRS-60



Air Displacement: 1700 l/min
Max Pressure: 15 bar
Voltage (v): 220/1
Power (w): 705
Cooling Liquid: R134 a
Connections: 3/4"
Net Weight: 35 Kg
Width X Height X Length:
410 x 482 x 600 mm

R19999⁰⁰

LIMITED STOCK